



NOVUS MANAGEMENT SYSTEM



AC computer unit

NMS AC X-TR-III



DIMENSIONS



Unit with the Microsoft Windows 10 IoT operating system and NOVUS MANAGEMENT SYSTEM AC software installed. Designed to work as a server or server/client station. Adapted to 24/7 operation.

Display	
Monitor outputs	1 x HDMI, 1 x Display Port, 1 x Dual link-DVI
Max resolution	3 x 4K UltraHD
Audio	
Audio output	1 x line(3.5mm), 1 x HDMI, 1 x Display Port
Network	
Network interface	3 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s
Przepustowość	Max network throughput: 450Mbit/s for each network card
Additional interfaces	
USB ports	4 x USB 3.2, 2 x USB 2.0 x USB 3.0
Operating system	
Operating system	Microsoft Windows 10 IoT
System language	Polish, English, Russian, Hungarian, others
Integration	
Dedicated for	NOVUS MANAGEMENT SYSTEM AC
Integrated devices	KDH-KS3012-IP, KDH-KS3024-IP, KDH-KS2000-IP-ELV, KDH-KS3000-IP-ELV, KDH-CADM500-FP, KDH-KZ3000FP-IP-M, KDH-KZ3000FP-IP-U, KDH-KZ3000-IP-M, KDH-KZ3000-IP-U, KDH-TA500CFP-IP-U/M/D, KDH-TA500C-IP-U/M/D, Kantech controllers (Entrapass Corporate or Global software required), NOVUS IP cameras of the 4000/6000/8000 series, NOVUS IP recorders of the 4000/6000 series, NOVUS 4000/6000 series multistandard recorders, ONVIF / RTSP IP cameras, NOVUS MANAGEMENT SYSTEM VSS IP Recorders, NMS IP Recorders, NOVUS MANAGEMENT SYSTEM AC Servers, SATEL Integra control panels, POLON 6000 fire alarm control panels, Net I/O Modules LANKOW-008, KDH-KS3012-IP-II, KDH-KS3024-IP-II
Installation parameters	
Dimensions (mm)	178 (W) x 452 (H) x 648 (D)
Weight	28 kg
Power supply	Built in 700W, with 230VAC input
Operating Temperature	5°C ~ 35°C
RACK Mount 19"	4U